

# Safety Data Sheet

## S Lava Ceramic

---

### SECTION 1: Identification

#### Product identifier

|                        |  |
|------------------------|--|
| Product name           | S Lava Ceramic                                       |
| Substance name         | Magnesium Silicate<br>$Mg_3Si_4O_{10}$               |
| Other names / synonyms | Fired S Lava Ceramic, S-Stone, Block Talc, Soapstone |

#### Recommended use of the chemical and restrictions on use

Technical Ceramic Components

#### Supplier's details

|           |  |
|-----------|--|
| Name      | Engineered Ceramics China Ltd  |
| Address   | Building 1, Xinlianhe Industrial Park,<br>Heyi, Shajing, Bao'an, Shenzhen,<br>China. |
| Telephone | +86-755-29902241   |
| Fax       | +86-755-29902499   |

#### Emergency phone number(s)

---

### SECTION 2: Hazard identification

This product is considered an article and does not pose any health hazard under normal use. The health effects listed below may be relevant when dust is generated during machining or other processing conditions.

#### Classification of the substance or mixture

Not a hazardous substance or mixture

#### GHS label elements, including precautionary statements

Not a hazardous substance or mixture

#### Other hazards which do not result in classification

Not a hazardous substance or mixture

---

### SECTION 3: Composition/information on ingredients

#### Components

##### 1. TALC

|               |            |
|---------------|------------|
| Concentration | 90 - 100 % |
|---------------|------------|

|                        |   |
|------------------------|---|
| Other names / synonyms | FRENCH CHALK; HYDROUS MAGNESIUM SILICATE; MINERAL GRAPHITE; NON-ASBESTIFORM TALC; NON-FIBROUS TALC; |
|------------------------|---|

# Safety Data Sheet

## S Lava Ceramic

CAS no.

SOAPSTONE; STEATITE; TALC; TALC (NON-ASBESTOS FORM); TALC powder; TALC, NON-ASBESTOS FORM, SILICA; TALCUM  
14807-96-6

---

### SECTION 4: First-aid measures

#### Description of necessary first-aid measures

|                         |   |
|-------------------------|---|
| General advice          | Hazard is principally that of a nuisance dust only as a byproduct of machining. Coughing or shortness of breath may occur in cases of excessive inhalation. |
| If inhaled              | Move to fresh air and consult with local medical personnel if discomfort persists.  |
| In case of skin contact | Wash affected area with soap and water and consult with local medical personnel if irritation persists.   |
| In case of eye contact  | Flush with tepid water for a minimum of 15 minutes and consult with local medical personnel if discomfort persists.   |
| If swallowed            | Administer water to dilute, but not if person is unconscious. Consult with local medical personnel if discomfort persists.                                  |

---

### SECTION 5: Fire-fighting measures

#### Suitable extinguishing media

Use any means suitable for extinguishing surrounding fire.

#### Special protective actions for fire-fighters

Use protective clothing and breathing equipment appropriate for the surrounding fire and to protect against the dust that may be dispersed in the air.

---

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Any dust from machining should be wet mopped or dry vacuumed.

---

### SECTION 7: Handling and storage

#### Precautions for safe handling

Any dust from machining should be wet mopped or dry vacuumed.

---

### SECTION 8: Exposure controls/personal protection

#### Control parameters

1. Silicates (less than 1% crystalline silica), Talc (containing no asbestos), respirable dust (CAS: 14807-96-6)

PEL (Inhalation): See Annotated Z-3 ppm (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

# Safety Data Sheet

## S Lava Ceramic

### 2. Silicates (less than 1% crystalline silica), Talc (containing no asbestos), respirable dust (CAS: 14807-96-6)

PEL (Inhalation): See Annotated Z-3 mg/m<sup>3</sup> (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 3. Silicates (less than 1% crystalline silica), Talc (containing no asbestos), respirable dust (CAS: 14807-96-6)

PEL (Inhalation): See Annotated Z-3 (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 4. Silicates (less than 1% crystalline silica), Talc (containing no asbestos), respirable dust (CAS: 14807-96-6)

REL (Inhalation): See Annotated Z-3 (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 5. Soapstone

PEL (Inhalation): See Annotated Z-3 ppm (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 6. Soapstone

PEL (Inhalation): See Annotated Z-3 mg/m<sup>3</sup> (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 7. Soapstone

PEL (Inhalation): See Annotated Z-3 (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### 8. Soapstone

REL (Inhalation): See Annotated Z-3 (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

### Appropriate engineering controls

Local or general exhaust ventilation and/or mister to control dust during machining is recommended.

### Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

Safety goggles in the presence of airborne dust.

#### Skin protection

Polymer gloves for prolonged dust exposure.

#### Respiratory protection

NIOSH/MSHA approved respirator for dust when exposure limit is exceeded.

---

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

|   |                                 |
|---|---------------------------------|
| Appearance/form                         | White or Gray Semi-Porous Solid |
| Odor                                    | Odorless                        |
| Odor threshold                          | N/A                             |
| pH                                      | N/A                             |
| Melting point                           | >1299°C (2370°F)                |
| Initial boiling point and boiling range | N/A                             |
| Flash point                             | N/A                             |
| Evaporation rate                        | N/A                             |
| Flammability (solid, gas)               | N/A                             |

# Safety Data Sheet

## S Lava Ceramic

|  |                    |
|--|--------------------|
| Upper/lower flammability limits        | N/A                |
| Upper/lower explosive limits           | N/A                |
| Vapor pressure                         | N/A                |
| Vapor density                          | N/A                |
| Relative density                       | 2.6-2.8 g/cc       |
| Solubility(ies)                        | Insoluble in Water |
| Partition coefficient: n-octanol/water | N/A                |
| Auto-ignition temperature              | N/A                |
| Decomposition temperature              | N/A                |
| Viscosity                              | N/A                |
| Explosive properties                   | N/A                |
| Oxidizing properties                   | N/A                |

---

### SECTION 10: Stability and reactivity

#### Chemical stability

Stable

---

### SECTION 11: Toxicological information

No Applicable Information Found

---

### SECTION 12: Ecological information

No Applicable Information Found

---

### SECTION 13: Disposal considerations

#### Disposal of the product

This material is not hazardous per 40 CFR 261. Consultation with federal, state and local officials is recommended before disposal.

---

### SECTION 14: Transport information

#### DOT (US)

Not dangerous goods

#### IMDG

Not dangerous goods

#### IATA

Not dangerous goods

---

### SECTION 15: Regulatory information

#### US FEDERAL

##### TSCA

CAS# 14807-96-6 is listed on the TSCA inventory.

##### SARA Section 302 Extremely Hazardous Substances

Substance Not Listed.

# Safety Data Sheet

## S Lava Ceramic

### Section 313

Substance Not Listed.

### OSHA:

None of the chemicals in this product are considered highly hazardous by OSHA.

### US STATE

**No Applicable Information Found**

### California Prop 65

No components on list.

---

## SECTION 16: Other information

### Further information/disclaimer

Although reasonable care has been taken to provide accurate and current information in preparation of this document, Superior Technical Ceramics extends no warranties, makes no representation and assumes no responsibility for any loss, damage, or injury of any kind which may result from reliance of information provided in this document by any person.