## **SECTION 1: Identification**

#### **Product identifier**

Product name Unfired S Lava

Substance name Hydrated Magnesium Silicate

 $Mg_3Si_4O_{10}(OH)_2$ 

Other names / synonyms S Lava, Naturally formed talc, S-Stone, Soap Stone

## Recommended use of the chemical and restrictions on use

Raw material for technical ceramic components.

## Supplier's details

Name Engineered Ceramics China Ltd Address Building 1, Xinlianhe Industrial

Park, Heyi, Shajing, Bao'an,

Shenzhen, China. +86-755-29902241 +86-755-29902499

Telephone Fax

**Emergency phone number(s)** 

## **SECTION 2: Hazard identification**

This product is considered an article and does not pose any health hazard under normal use. The health effects listed below may be relevant when dust is generated during machining or other processing conditions.

#### Classification of the substance or mixture

Not a hazardous substance or mixture

#### GHS label elements, including precautionary statements

Not a hazardous substance or mixture

#### Other hazards which do not result in classification

Not a hazardous substance or mixture

# **SECTION 3: Composition/information on ingredients**

## Components

1. TALC

Concentration 100 - 100 %

Other names / synonyms FRENCH CHALK; HYDROUS MAGNESIUM SILICATE; MINERAL

GRAPHITE; NON-ASBESTIFORM TALC; NON-FIBROUS TALC;

SOAPSTONE; STEATITE; TALC; TALC (NON-ASBESTOS FORM); TALC

powder; TALC, NON-ASBESTOS FORM, SILICA; TALCUM

CAS no. 14807-96-6

#### **SECTION 4: First-aid measures**

## Description of necessary first-aid measures

General advice Naturally occurring mined mineral. Dust from machining or component

pulverization can create nuisance dust leading to eye, nose, throat and/or

skin irritation.

If inhaled Move to fresh air and consult with local medical personnel if discomfort

persists.

In case of skin contact Wash affected area with soap and water and consult with local medical

personnel if irritation persists.

In case of eye contact Flush with tepid water for a minimum of 15 minutes and consult with local

medical personnel if discomfort persists.

## **SECTION 5: Fire-fighting measures**

## Suitable extinguishing media

Use any means suitable for extinguishing surrounding fire.

#### Special protective actions for fire-fighters

Use protective clothing and breathing equipment appropriate for the surrounding fire and to protect against the dust that may be dispersed in the air.

## **SECTION 6: Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

Any dust from machining should be wet mopped or dry vacuumed.

## Methods and materials for containment and cleaning up

Any dust from machining should be wet mopped or dry vacuumed.

## **SECTION 7: Handling and storage**

## Precautions for safe handling

Any dust from machining should be wet mopped or dry vacuumed.

## **SECTION 8: Exposure controls/personal protection**

#### **Control parameters**

1. Silicates (less than 1% crystalline silica), Talc (containing no asbestos), respirable dust (CAS: 14807-96-

PEL (Inhalation): See Annotated Z-3 ppm (OSHA) OSHA Annotated Table Z-1, www.osha.gov

# 2. Silicates (less than 1% crystalline silica), Talc (containing no asbestos), respirable dust (CAS: 14807-96-

6)

PEL (Inhalation): See Annotated Z-3 mg/m3 (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

# 3. Silicates (less than 1% crystalline silica), Talc (containing no asbestos), respirable dust (CAS: 14807-96-

6)

PEL (Inhalation): See Annotated Z-3 (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

# 4. Silicates (less than 1% crystalline silica), Talc (containing no asbestos), respirable dust (CAS: 14807-96-

6)

REL (Inhalation): See Annotated Z-3 (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

## 5. Soapstone

PEL (Inhalation): See Annotated Z-3 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

## 6. Soapstone

PEL (Inhalation): See Annotated Z-3 mg/m3 (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

#### 7. Soapstone

PEL (Inhalation): See Annotated Z-3 (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

## 8. Soapstone

REL (Inhalation): See Annotated Z-3 (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

#### Appropriate engineering controls

Local or general exhaust ventilation and/or mister to control dust during machining is recommended.

## Individual protection measures, such as personal protective equipment (PPE)

#### Eve/face protection

Safety goggles in the presence of airborne dust.

#### Skin protection

Polymer gloves for prolonged dust exposure.

## Respiratory protection

NIOSH/MSHA approved respirator for dust when exposure limit is exceeded.

## **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance/form Off-white solid Odor Odorless
Odor threshold N/A
pH N/A

Melting point >1299°C (2370°F)

Initial boiling point and boiling range N/A
Flash point N/A
Evaporation rate N/A
Flammability (solid, gas) N/A

Partition coefficient: n-octanol/water N/A
Auto-ignition temperature N/A
Decomposition temperature N/A
Viscosity N/A
Explosive properties N/A
Oxidizing properties N/A

## **SECTION 10: Stability and reactivity**

## **Chemical stability**

Stable

## **SECTION 11: Toxicological information**

No Applicable Information Found

## **SECTION 12: Ecological information**

No Applicable Information Found

## **SECTION 13: Disposal considerations**

### Disposal of the product

This material is not hazardous per 40 CFR 261. Consultation with federal, state and local officials is recommended before disposal.

# **SECTION 14: Transport information**

## DOT (US)

Not dangerous goods

#### **IMDG**

Not dangerous goods

## **IATA**

Not dangerous goods

## **SECTION 15: Regulatory information**

#### **US FEDERAL**

#### **TSCA**

CAS# 14807-96-6 is listed on the TSCA inventory.

## **SARA Section 302 Extremely Hazardous Substances**

Substance Not Listed.

Section 313

Substance Not Listed.

OSHA:

None of the chemicals in this product are considered highly hazardous by OSHA.

## **US STATE**

No Applicable Information Found

California Prop 65

No components on list.

# **SECTION 16: Other information**

## Further information/disclaimer

Although reasonable care has been taken to provide accurate and current information in preparation of this document, Superior Technical Ceramics extends no warranties, makes no representation and assumes no responsibility for any loss, damage, or injury of any kind which may result from reliance of information provided in this document by any person.